


## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>5</sup> : <b>F02M 29/06, F01N 7/08</b>	<b>A1</b>	(11) International Publication Number: <b>WO 94/02735</b> (43) International Publication Date: <b>3 February 1994 (03.02.94)</b>
<p>(21) International Application Number: <b>PCT/KR93/00060</b></p> <p>(22) International Filing Date: <b>21 July 1993 (21.07.93)</b></p> <p>(30) Priority data: 1992-13507                      22 July 1992 (22.07.92)                      <b>KR</b></p> <p>(71)(72) Applicant and Inventor: <b>CHO, Byoung, Min [KR/KR];</b> 753-15, Mok 4-Dong, Yang Cheon-Ku, Seoul 158-050 (KR).</p> <p>(81) Designated States: <b>AU, BR, CA, JP, RU, US, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).</b></p>	<p><b>Published</b> <i>With international search report.</i> <i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i></p>	

## (54) Title: AIR WHIRLPOOL GENERATOR FOR AN INTERNAL COMBUSTION ENGINE

## (57) Abstract

In a background art using the air whirlpool generation technologies, there was a turbulence chamber (whirlpool chamber type) engine in the past and at present, a further developed DOHC engine having the type of horizontal whirlpool generation within a cylinder. Further, it is known scientifically that effects for improvement in performances of the engines, saving of energy, reduction of smoke pollution and reduction of engine noise were obtained by mounting the air whirlpool generator on the internal combustion engine using various fuels including gasoline, diesel oil, liquified petroleum gas, alcohol, hydrogen gas, etc. The present invention has the benefits that with an outer structure of a radial wing (7) generating whirlpool of the centrifugal force and with an inner structure composed of a central air separation plate (6) having a cyclone aperture (5) of predetermined diameter, generating the whirlpool of the centripetal force, air flowing at high speed is instantaneously separated and the whirlpool of the centripetal force with a high-speed cyclone center is obtained so as to improve the combustion performances of the engines.



**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	FR	France	MR	Mauritania
AU	Australia	GA	Gabon	MW	Malawi
BB	Barbados	GB	United Kingdom	NE	Niger
BE	Belgium	GN	Guinea	NL	Netherlands
BF	Burkina Faso	GR	Greece	NO	Norway
BG	Bulgaria	HU	Hungary	NZ	New Zealand
BJ	Benin	IE	Ireland	PL	Poland
BR	Brazil	IT	Italy	PT	Portugal
BY	Belarus	JP	Japan	RO	Romania
CA	Canada	KP	Democratic People's Republic of Korea	RU	Russian Federation
CF	Central African Republic	KR	Republic of Korea	SD	Sudan
CG	Congo	KZ	Kazakhstan	SE	Sweden
CH	Switzerland	LI	Liechtenstein	SI	Slovenia
CI	Côte d'Ivoire	LK	Sri Lanka	SK	Slovak Republic
CM	Cameroon	LU	Luxembourg	SN	Senegal
CN	China	LV	Latvia	TD	Chad
CS	Czechoslovakia	MC	Monaco	TG	Togo
CZ	Czech Republic	MG	Madagascar	UA	Ukraine
DE	Germany	ML	Mali	US	United States of America
DK	Denmark	MN	Mongolia	UZ	Uzbekistan
ES	Spain			VN	Viet Nam
FI	Finland				

## AIR WHIRLPOOL GENERATOR FOR AN INTERNAL COMBUSTION ENGINE

TECHNICAL FIELD

The present invention relates to an air whirlpool generator for an air-suction hose and an exhaust pipe of an internal combustion engine. More particularly, the present invention relates to improvements in combustion performances of various engines using the air whirlpool generation technologies, in which air-fuel mixture and combustion reaction are improved by mounting on the air-suction hose the air whirlpool generator having the same condition as that of the existing direction of the air whirlpool generation designed in an air-cleaner box of the internal combustion engine, and the exhaust gas is discharged at high speed by mounting the equal type of air whirlpool generator on the exhaust passage from the engine.

BACKGROUND ART

In a background art using the air whirlpool generation technologies, there was a turbulence chamber(whirlpool chamber type) engine in the past and at present, a further developed DOHC engine having the type of horizontal whirlpool generation within a cylinder.

Also, it is known and disclosed in several patents to provide a variety of air whirlpool generator on air-suction port such as air-cleaner, carburetor or suction pipe and on air exhausting port, of various internal combustion engines and an automobile engine so as to improve performances of the engines. Such patents as are known in the art are U.S. Patent No. 2,017,043, U.S.

Patent No. 3,877,907 and U.S. Patent No. 4,962,642, Japanese Patent Publication No. 58-13122, Korean Utility Model Publication No. 76-1369, and Korean Patent No. 411,425, and the technologies disclosed in the patents are  
5 being actually used in the various combustion engines and the automobile engine.

Further, it is known scientifically that effects for improvement in the performances of the engines, saving of energy, reduction of smoke pollution and reduction of  
10 engine noise were obtained by mounting the air whirlpool generator on the combustion engine using various fuels including gasoline, diesel oil, liquefied petroleum gas, alcohol, hydrogen gas, etc.

#### DISCLOSURE OF INVENTION

15 It is known in several patents that combustion performances of the engines were improved by using the air whirlpool generator mounted on the air-suction port of the air passing through an air filter and the air-exhausting port, of the various combustion engines.

20 There are "+" type of whirlpool generator, propeller type of whirlpool generator, radial fan type of whirlpool generator, spiral pipe type of whirlpool generator and the whirlpool generator using a radial plate.

The air whirlpool generator according to the present  
25 invention is different from that of the prior patents and known technologies and the present invention has the benefits that with an outer structure of a radial wing generating whirlpool of the centrifugal force and with an inner structure composed of a central air separation plate

having a cyclone aperture of predetermined diameter, generating the whirlpool of the centripetal force, air flowing at high speed is instantaneously separated and the whirlpool of the centripetal force with a high-speed  
5 cyclone center is obtained so as to improve the combustion performances of the engines.

Namely, the present invention is a technology of generating the air whirlpool by obtaining the centripetal force with a high-speed cyclone center by fixedly mounting  
10 the air whirlpool generator on the air-suction port of the air passing through an air filter or the air- suction hose and the exhaust pipe or a tail pipe of muffler, respectively. The present invention is characterized in that it has the structure for generating the centrifugal  
15 whirlpool of radial wings 7 increasing at the first stage instantaneous speed of a running fluid by mounting a circular ring type of an orifice 2 for the purposes of Venturi effects adequate to a pipe 1 in which high-speed air flows, connected with a fixing support pin 4  
20 maintaining regular intervals from such orifice, and the structure for generating the whirlpool, composed of the structure for generating the whirlpool of the centripetal force having a central air separation plate 6 with a cyclone aperture 5 of predetermined diameter. The present  
25 invention is also characterized in that with the construction mentioned above, effects of discharging the whirlpool of the centripetal force with the cyclone center at high speed are obtained by instantaneously separating the air flowing at high speed into the centrifugal

whirlpool and the centripetal whirlpool.

Such principle is equal to the principle of firing a ball cartridge with the high-speed whirlpool from M16 barrel, and in the principle, effects of discharging  
5 centripetal whirlpool with the cyclone center were utilized in generating the air whirlpool of the air-suction hose of the engines. By mounting the air whirlpool generator on the air-suction hose of each internal combustion engine, mixture rate between the air and the  
10 fuel including gasoline, diesel oil, liquefied petroleum gas, alcohol, hydrogen gas, etc., is increased and the combustion reaction rate is improved so that output energy (applying the principle of  $E = M C^2$ ) of various engines is increased. In the same manner as mentioned above, by  
15 mounting the air whirlpool generator on the exhaust hose such as exhaust pipe or tail pipe of muffler, the exhaust gas is discharged at high speed to improve the combustion performances of the engines.

The air whirlpool generator according to the present  
20 invention is a technology conceived with the application of the whirlpool of the centripetal force having the strong cyclone center to achieve the effects for improvements in the engines performances, energy saving, reduction of smoke pollution, improvements in incomplete  
25 combustion and reduction of the engine noise.

#### BRIEF DESCRIPTION OF DRAWINGS

Fig. 1 is a perspective view of an air whirlpool generator for an internal combustion engine according to the present invention.

Fig. 2 is a bottom perspective view of the air whirlpool generator according to the present invention.

Fig. 3 is a reference view showing the air whirlpool generator in use.

5 Fig. 4 is a top view of the air whirlpool generator according to the present invention.

Fig. 5 is a bottom view of the air whirlpool generator according to the present invention.

Fig. 6 is a front elevational view of the air  
10 whirlpool generator according to the present invention, and is a rear elevational view thereof, which is symmetrical.

Fig. 7 is a right-side elevational view of the air whirlpool generator according to the present invention,  
15 and is a left-side elevational view thereof, which is symmetrical.

Fig. 8 is a view taken on line A-A of Fig. 6.

#### BEST MODE FOR CARRYING OUT THE INVENTION

As a method for mounting an air whirlpool generator  
20 according to the present invention on both sides of air-suction hose and exhaust pipe or tail pipe of muffler, the air whirlpool generator according to the present invention is mounted firstly at an air passage passing through an air filter to improve combustion performances of an  
25 internal combustion engine using various fuels and to obtain the effects for reduction of smoke pollution and for energy saving, and the air whirlpool generator according to the present invention is mounted on the exhaust pipe so that the exhaust gas can be discharged at

high speed. Such improvements in the engine performances will lead to energy saving and reduction of smoke pollution.

#### INDUSTRIAL APPLICABILITY

5       An air whirlpool generator according to the present invention can be applied to any air-suction port and air-exhausting port of various internal combustion engines using gasoline, diesel oil, liquefied petroleum gas, alcohol, hydrogen gas and other gas. The air whirlpool  
10 generator is used mostly for improvement in combustion performances of engines, energy saving and reduction of smoke pollution. For manufacturing the product according to the present invention, composite materials including metal, ceramic, reinforced plastic, etc., can be used.



CLAIMS

1. An air whirlpool generator for an internal combustion engine which was fixedly mounted on an air-  
5 suction port including an air-suction hose and an exhaust pipe or tail pipe of muffler, wherein said air whirlpool generator comprising;

an outer structure having a plurality of radial wings for generating whirlpool of centrifugal force  
10 connected fixedly with a fixing support pin 4 maintaining predetermined intervals on an orifice 2 having an air aperture 3 for increasing instantaneous speed of a running fluid for Venturi effects adequate to the diameter of said air-suction hose or pipe 1, and

15 an inner structure having a cyclone aperture 5 of predetermined diameter on an air separation plate 6 in a center portion for generating whirlpool of the centripetal force.

1/5

FIG.1






FIG.2



2/5

FIG. 3

0300



3/5

FIG. 4





FIG. 5



4/5

FIG. 6






FIG. 7



5/5

FIG. 8



## INTERNATIONAL SEARCH REPORT

International application No.

PCT/KR 93/00060

## A. CLASSIFICATION OF SUBJECT MATTER

IPC<sup>5</sup>: F 02 M 29/06; F 01 N 7/08

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC<sup>5</sup>: F 02 M 29/04, 29/06, 35/10; F 01 N 1/12, 5/04, 7/08; F 02 B 27/04

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US, A, 3 938 967 (REISSMÜLLER) 17 February 1976 (17.02.76), totality.	1
A	GB, A, 645 812 (THOMPSON, FREEMAN) 08 November 1950 (08.11.50), totality.	1
A	CH, A, 284 184 (KUHN) 01 November 1952 (01.11.52), totality.	1
A	DE, A1, 2 706 892 (FORD-WERKE AG) 25 August 1977 (25.08.77), totality.	1
A	US, A, 4 222 456 (KASPER) 16 September 1980 (16.09.80), totality.	1
	----	

☐ Further documents are listed in the continuation of Box C.☒ See patent family annex.

## \* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&amp;" document member of the same patent family

Date of the actual completion of the international search

24 November 1993 (24.11.93)

Date of mailing of the international search report

02 December 1993 (02.12.93)

Name and mailing address of the ISA/ AT  
 AUSTRIAN PATENT OFFICE  
 Kohlmarkt 8-10  
 A-1014 Vienna  
 Facsimile No. 1/53424/535

Authorized officer

Pippan e.h.  
 Telephone No. 1/533424/359

Form PCT/ISA/210 (second sheet) (July 1992)

INTERNATIONAL SEARCH REPORT  
Information on patent family members

International application No.

PCT/KR 93/00060

Im Recherchenbericht angeführtes Patentdokument Patent document cited in search report Document de brevet cité dans le rapport de recherche	Datum der Veröffentlichung Publication date Date de publication	Mitglied(er) der Patentfamilie Patent family member(s) Membre(s) de la famille de brevets	Datum der Veröffentlichung Publication date Date de publication
US A 3938967	17-02-76	AT A 834/75 AT B 332682 BR A 7501381 CA A1 1016826 CH A 577113 DD C 117265 DE A1 2510677 DE B2 2510677 DE C3 2510677 DK A 1289/75 DK B 139394 DK C 139394 ES A1 436038 FI A 750818 FR A1 2265997 GB A 1496040 HU F 171821 IL A0 46868 IL A1 46868 IT A 1033363 JP A2 50130926 JP B4 55017229 NL A 7502065 NO A 750607 SE A 7502064 SE B 400349 SE C 400349 YU A 392/75 YU B 36062 ZA A 7500377	15-01-76 11-10-76 30-11-76 06-09-77 30-06-76 05-01-76 02-10-75 29-05-80 16-04-81 30-09-75 12-02-79 23-07-79 01-01-77 30-09-75 24-10-75 21-12-77 28-03-78 22-05-75 31-08-77 10-07-79 16-10-75 09-05-80 01-10-75 30-09-75 30-09-75 20-03-78 29-06-78 30-04-81 13-11-81 28-01-76
GB A 645812		keine - none - rien	
CH A 284184		keine - none - rien	
DE A1 2706892	25-08-77	AU A1 22059/77 AU B2 511072 CA A1 1060735 DE C2 2706892 ES A1 456130 ES A5 456130 FR A1 2341748 FR B1 2341748 GB A 1568845 JP A2 52102936 US A 4094291	17-08-78 24-07-80 21-08-79 11-10-84 01-02-78 28-02-78 16-09-77 18-06-82 04-06-80 29-08-77 13-06-78
US A 4222456	16-09-80	JP A2 53132633	18-11-78